
grip lock

Best selling versatile clip mounts to any surface. Ideal for air conditioning line sets.



ΕN

| VEV | FEAT | IDEC |
|-----|------|------|
| NET | FEAL | UNES |
| | | |

- Fits directly to a wall or solid ceiling
- Hinged for rapid pipe installation
- Space for electrical cables and condensate hose
- Zinc and colour passivated to resist corrosion

• Wide metal components for good pipe support

| SPECIFICATIONS | | | | | |
|--------------------------------|-------------------------------|--|--|--|--|
| Materials of construction | Zinc passivated mild steel | | | | |
| Max. temp | 1000°C | | | | |
| Max. rec. distance per clip | 1.2m | | | | |

| Description | Liquid* | Gas* | Width (mm) | Height (mm) | Part No. | Pack Qty |
|-------------|---------|---------------|---------------|----------------|----------|----------|
| Size 1 | 1/4″ | 1/2″ | 54 | 30 | B6186 | 10 |
| Size 2 | 3/8″ | 5/8″ | 60 | 32 | B6187 | 10 |
| Size 3 | 1/2″ | 7/8″ | 67 | 37 | B6188 | 10 |
| Size 4 | 5/8″ | 1 1/8″ | 80 | 46 | B6189 | 10 |


* Approximate pipe sizes (allowing for 10mm insulation)


Material: BS EN 10230:2006. Coating: BS EN 12329:2000





Ŷ

For further details please refer to our website aspenpumps.com/xtra









Information correct at time of going to press.



